Spa / Ease 150 Cover Lifter

## Installation Instructions

#### Step #1

Position your spa cover (in the closed position) on the spa with all four corners evenly matched with the corners of your spa.

### Step #2

Position the Pivot Arm on the ground (short side on bottom) with a Plastic Pivot (flat side out) on each side of the hole. Next position Pivot Arm next to hole on the exterior side of the Undermount Base with Pivot arm running away from the base. Pass a Washer and a Hex Screw first thru the Pivot Arm and into hole at the end of the Base and then with a Washer and a Nut secure tightly. Attach Large Plastic Pivot Caps.

Repeat on the other side. (See Fig 2).

#### Step #3

Slide the Under-Mount Base Bracket under the spa with the Pivot Arm in the upright position and pointing away from spa. The edge of the Under-Mount Base should be 7" from the furthest point on your spa (See Fig 1). Repeat on the other side.

#### Step #4

Insert the LONG end of the Crossbar Arm into each of the Pivot Arms then use the non-fluted Center Extension to connect each of the Crossbar Arms (See Fig 3). On larger spas use the additional Center Extension that is fluted (See Fig3 A).

#### Step #5

Lay the attached Crossbar Arms with Extension(s) along the top of the Spa Cover. Adjust so that the Crossbar Arms are approximately 1/2" away of the center of the cover's hinge (See Fig 4).

#### Step #6


Attach the Pivot Arms to Crossover Arms and the Crossover Arms to the Center Extensions using the Self-Tapping Screws. When using both Extensions, rotate them so that the Screws are positioned at the identical angle to the Crossover Bars, so that the Screw heads do not damage the cover during operation.


## CAUTION!


DO NOT USE THE SpaEase 150 IN HIGH WIND CONDITIONS (ABOVE 10 MPH.) SPA COVER CAN BLOW OVER AND DAMAGE **PROPERTY OR CAUSE INJURY** 


#### WARRANTY REGISTRATION FORM

Model Name: Purchased From: Dealer ( )		
Dealer Name:		_ State:
Zip Code:		
Address:		
Owners Name:		
Address:		
State: Zip Code	:	
Phone #:		
Hot Tub Products • (860) 46 2 Toelles Road, Wallingford	-	










# Spa LEase 150 Cover Lifter

Installation Instructions









ITEM	QTY	DESCRIPTION
А	2	Under-Mount Base Brackets
В	2	Bottom Pivot Arms
С	2	Crossbar Arms
D	2	Center Extensions (1 Fluted)
E	12	Self-Tapping Screws
F	4	Large Plastic Pivots Caps
G	4	Large Black Plastic Caps
Н	2	Hex Screw
1	4	Flat Washer
J	2	Nut
К	12	Small Black Plastic Caps

Hot Tub Products • (860) 469-2580 • Info@HotTubProducts.com 20 Commerce Dr. North Branford, CT 06471 • www.HotTubProducts.com